



2960 | 2961 | 2962



**Clip board**  
see also page 92



**Wire basket for small items**  
600 x 140 x 200 mm



2970 | 2971 | 2972



**Deposit locks**  
made of high-quality plastic, to be operated easily and safely. Suitable for 1 Euro coins.



2980 | 2981 | 2982

**Wall securing chain**  
for deposit lock, length 1.20 m.

## Cash and carry carts

Nesting trolleys, thereby reducing storage space by 75%.

Tubular steel construction, powder coated, platform made of anti-skid waterproof plywood boards.

2 castor wheels and 2 fixed wheels, solid rubber tyres.

Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

## 2960 | 2961 | 2962

Platform height: 265/310 mm  
Total width: 650/750/850 mm

## 2970 | 2971 | 2972

as 2960/2961/2962, but with 2 shelves.

Shelf heights:  
with wheel-Ø 160 = 265/775 mm  
with wheel-Ø 200 = 310/820 mm

Capacity upper shelf = 80 kg.

## 2980 | 2981 | 2982

as 2960/2961/2962, but instead of tubular pushbar 2 lateral frames, 680 mm high, on the side of the fixed wheels also 2 lateral frames, 500 mm high.

Platform interior width: 435/535/635 mm.

	Order No.	Capacity kg	Wheel Ø mm	Platform size L x W mm
<b>Cash and carry carts</b>	2960	400	160	850 x 500
	2961	500	200	1000 x 600
	2962	500	200	1000 x 700
	2970	400	160	850 x 500
	2971	500	200	1000 x 600
	2972	500	200	1000 x 700
	2980	400	160	850 x 500
	2981	500	200	1000 x 600
	2982	500	200	1000 x 700
<b>Clip board</b>	1290	-	-	-
<b>Wire basket</b>	1291	-	-	-
<b>Deposit locks</b>	2910	-	-	-
<b>Wall securing chain</b>	2913	-	-	-



3270



3280 | 3282



3285



3290 | 3291



3286



3191

## Mobile tilting stands

for plastic boxes, steel plate boxes, wire baskets etc., adjustable in height and mobile.

Sectional steel-/ tubular construction with steel plate platform. Powder-coated blue RAL 5007.

4 castors with TPE tyres, hubs with bush bearing, 2 wheels with locks.

### 3270

Steel plate platform with all side rim, 20 mm high. Not inclinable, adjustable in height in intervals of 25 mm.

### 3280 | 3282

Steel plate platform with single-sided lay-on edge, inclinable by 15° und 30°, adjustable in height in intervals of 25 mm.

### 3285

Steel plate platform with single-sided lay-on edge, inclinable by 15° und 30°, continuously adjustable in height via rack and pinion jack, even under load. 2 telescopic pillars.

### 3290 | 3291

Steel plate platform with single-sided lay-on edge, inclinable by 15° und 30°, continuously adjustable in height, rotatable and lockable, with pneumatic lowering damping.

### 3286

Steel plate platform with single-sided lay-on edge, inclinable by 15° und 30°, continuously adjustable in height via hydraulic pump, even under load. Operated via pedal, precisely adjustable via lowering valve.

## Roller support 3191

to support long materials on saws, presses, drills etc. Continuously adjustable in height, rotatable and lockable, with pneumatic lowering damping. Mobile.

Supporting roller of tubular steel 60 mm Ø, ball bearing mounted. Loose gravity-stops on both sides 20 mm above top edge of roller (automatically turn away for wide work pieces).

4 castor wheels with locks. Flat packed for easy self assembly.

**Guarantee** for 3191, 3286 and 3290/3291 2 years.

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Height adjustable from - to mm	Net weight kg	
Mobile tilting stands	3270	150	75	605 x 405	720 - 970	18	
	3280	150	75	510 x 410	500 - 770	17	
	3282	150	75	510 x 410	750 - 1100	19	
	3285	250	125	750 x 450	670 - 1025	36	
	3286	250	125	750 x 450	720 - 1070	39	
	3290	150	75	510 x 410	510 - 700	23	
	3291	150	75	510 x 410	720 - 1070	25	
Roller support	3191	150	75		730 - 1070	21	



### Wheel lock "Double stop"

for castor wheels, prevents rolling away of trolleys.

Wheel-Ø	Order no.
125	1284
160	1285/160
200	1285/200
220 air	1283



### Wheels with pneumatic tyres

220 x 70 mm, Capacity 400 kg. Smooth running on rough surfaces, esp. outdoors. Available for trolley width from 600 mm.

Extra price compared to standard wheels.

Wheel-Ø	Order no.
125	1098
160	1099
200	1100



### Wheels with blue-grey solid rubber tyres

non-marking (trackless)

Extra price compared to standard wheels.

Wheel-Ø	Order no.
125	2185
160	2186
200	2187



### Wheels with electric conductive solid rubber tyres (antistatic).

Extra price compared to standard wheels.

Wheel-Ø	Order no.
125	2191
160	2192
200	2193



### Polyamide wheels

high carrying-capacity. Smooth running on even floors. Largely resisting to humidity, salt, acids and caustic solutions.

Extra price compared to standard wheels.

Wheel-Ø	Order no.
125	1295
160	1296
200	1286



### Wheels with elastic tyres

Wheels with elastic tyres and ball bearing. Easy, smooth running, high durability.

Wheel-Ø	Order no.
125	12850
160	12860
200	12870



### Wheels with polyurethane tyres

200 x 50 mm, hubs with roller bearings, smooth, silent running, resisting to many aggressive media.

Order no.	
2181	



### Protective edge

of plastic profile for perimeter of base frame.

Order no.	
1289	



### Protective wheels

50 mm Ø made of light grey plastic

total width = platform + 80 mm


Order no.	
1299	



### Zinc sheet metal platform

zinc coated steel sheet edged over the platform.

Order no.	Platform
1280	850 x 500
1280	1000 x 600
1281	1000 x 700
1281	1200 x 800



### 4 castor wheels

instead of 2 castor and 2 fixed wheels, high manoeuvrability, easily steerable into all directions, limited directional stability.

Order no.	
1288	



### Wire basket

for small items, powder coated alu-silver.

L x D x H:  
600 x 140 x 200 mm

Order no.	
1291	



### Clip board

Upright format DIN A 4, wood with paper clamp and pencil case.

Order no.	
1290	

Broadsize A 4, Wood with paper clamp and pencil case.

Order no.	
1390	



### Electric drive unit 2200

Electric drive as a fit-on unit for all pushbar carts, openside platform carts, box carts, table top carts, shelved carts etc. with a wheel-Ø of 200 mm and width from 500 mm.

Drive complete with batteries and charging device.

Order no.	
2200	

Compact unit, easily to be assembled. Operating switch to be clamped to pushbar, connection with plug-in helix cable. Speed fully adjustable, for forward and reverse gears.

**Guarantee: 12 months**