

ESD TROLLEYS

Open carts, panelled end platform carts, table top carts and shelved trolleys in electric static discharge construction • ESD = Electrostatic Discharge • ESD trolleys save high quality and sensitive goods from damage of electric discharge • Modular system in fetra-Insert-and-Bolt Principle • Powder coated slate grey RAL 7015 • HPL composite shelves according to DIN 68765 • 2 castor wheels and 2 fixed wheels, solid rubber tyres, hubs equipped with roller bearings • electric static discharge • Castors with wheel locks



ESD-TROLLEYS



Electric static discharge construction (ESD = Electrostatic Discharge).

Tubular steel and sectional steel welded, conductive powder coating, slate grey. Screw and plug type construction.

HPL composite shelves according to DIN 68765, light grey.

2 castors and 2 fixed wheels, solid rubber tyres, 160 x 40 or 200 x 50mm, hubs with ball bearing.

Castors with wheel locks, according to European Standard EN1757-3 (safety of platform trolleys).

Platform height:

Solid rubber 160 Ø = 220 mm,

Solid rubber 200 Ø = 270 mm.



9500 | 9501 | 9502 | 9503 Open carts



9510 | 9511 | 9512 | 9513 Panelled end platform carts

Panelled end platform carts

Ends made of wire lattice 50 x 50 x 4 mm.

Height: 500 mm.

Table top carts

9400

Solid rubber tyres 160 x 40mm.
Level heights 220/865.



9400 | 9401 | 9402 | 9403 Table top carts

9401 | 9402 | 9403

Level heights:

Solid rubber: 270/905 mm

Capacity of upper shelf 200 kg.



9420 | 9422 | 9423 Table top carts

9420

Solid rubber tyres 160 x 40mm.
Level heights 220/550/865.

9422 | 9423

Level heights:

Solid rubber: 270/905 mm.

Capacity of upper and middle shelf 200 kg.

	Order no.	Capacity kg	Wheel Ø mm	Outside dimensions L x W x H mm	Platform size L x W mm	Net weight kg	
Open carts	9500	400	160	970 x 500 x 950	850 x 500	24	
	9501	500	200	1120 x 600 x 990	1000 x 600	30	
	9502	500	200	1120 x 700 x 990	1000 x 700	33	
	9503	500	200	1320 x 800 x 990	1200 x 800	38	
Panelled end platform carts	9510	400	160	970 x 500 x 950	850 x 500	26	
	9511	500	200	1120 x 600 x 990	1000 x 600	34	
	9512	500	200	1120 x 700 x 990	1000 x 700	37	
	9513	500	200	1320 x 800 x 990	1200 x 800	43	
Table top carts	9400	400	160	1040 x 500 x 865	850 x 500	38	
	9401	500	200	1190 x 600 x 905	1000 x 600	47	
	9402	500	200	1190 x 700 x 905	1000 x 700	52	
	9403	500	200	1390 x 800 x 905	1200 x 800	61	
	9420	400	160	1040 x 500 x 865	850 x 500	51	
	9422	500	200	1190 x 700 x 905	1000 x 700	70	
	9423	500	200	1390 x 800 x 905	1200 x 800	82	

Accessories on page 92



ESD TROLLEYS



1840 | 1841



1850 | 1851



1860 | 1861



1870 | 1871



1880 | 1881

Electric static discharge construction (ESD = Electrostatic Discharge).
Tubular steel and sectional steel welded, conductive powder coating, slate grey. Screw and plug type construction.
HPL composite shelves according to DIN 68765, light grey. Shelves with rim 5 mm high, boxes with rim 45 mm high.
2 castor wheels and 2 fixed wheels, solid rubber tyres, hubs equipped with roller bearings, ESD.
Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).
Total length: 980/1130 mm
Total height: 1020 mm
Interior measurement of boxes:
1860/1870/1880: 810 x 445 x 45 mm
1861/1871/1881: 960 x 545 x 45 mm
Capacity of upper and middle shelves 80 kg.

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	No. of shelves	Shelf heights mm	Net weight kg
ESD trolleys	1840	250	125	850 x 500	2	195, 820	30
	1841	250	125	1000 x 600	2	195, 820	39
	1850	250	125	850 x 500	3	195, 508, 820	39
	1851	250	125	1000 x 600	3	195, 508, 820	54
	1860	250	125	850 x 500	2	195, 820	29
	1861	250	125	1000 x 600	2	195, 820	36
	1870	250	125	850 x 500	2	195, 820	30
	1871	250	125	1000 x 600	2	195, 820	38
	1880	250	125	850 x 500	3	195, 508, 820	39
	1881	250	125	1000 x 600	3	195, 508, 820	48



Electric static discharge construction (ESD = Electrostatic Discharge).

Tubular steel and sectional steel welded, conductive powder coating, slate grey. Screw and plug type construction.

HPL composite shelves according to DIN 68765, light grey.

2 castor wheels and 2 fixed wheels, solid rubber tyres, hubs equipped with roller bearings, ESD.

Castors with wheel locks, according to the European Standard EN 1757-3 (safety of platform trolleys).

Capacity per shelf 80 kg.



9100 | 9101



9200 | 9201

Shelves

Additional charge or price reduction for shelves including 1 pair of support brackets.

Size mm	Order no.
850 x 500	E9100ETAW
1000 x 600	E9101ETAW
1000 x 700	E9302ETAW
1200 x 800	E9303ETAW

Boxes

instead of shelves, made from conductive composite board according to DIN 68765, light grey. Box height 60 mm, clear height 45 mm.

Size	850 x 500 mm
	1000 x 600 mm
	1000 x 700 mm
	1200 x 800 mm

Add „K” and amount of boxes to the order number, e. g., „9100 K3”.

Inside dimensions of boxes:

850 x 500mm =	810 x 445mm
1000 x 600mm =	960 x 545mm
1000 x 700mm =	960 x 645mm
1200 x 800mm =	1160 x 745mm

Capacity per box 80 kg.



9301 | 9302 | 9303



9341 | 9342 | 9343



	Order no.	Capacity kg	Wheel-Ø mm	Platform size LxW mm	Total height mm	No. of shelves	Shelf heights mm	Net weight kg
ESD trolleys	9100	250	160	850 x 500	1055	3	225, 585, 945	42
	9101	250	200	1000 x 600	1100	3	270, 630, 990	57
	9200	250	160	850 x 500	1455	4	225, 585, 945, 1305	48
	9201	400	200	1000 x 600	1500	4	270, 630, 990, 1350	65
	9301	400	200	1000 x 600	1800	4	270, 700, 1100, 1500	69
	9302	400	200	1000 x 700	1800	4	270, 700, 1100, 1500	76
	9303	400	200	1200 x 800	1800	4	270, 700, 1100, 1500	109
	9341	500	200	1000 x 600	1800	5	270, 600, 900, 1200, 1500	75
	9342	500	200	1000 x 700	1800	5	270, 600, 900, 1200, 1500	87
	9343	500	200	1200 x 800	1800	5	270, 600, 900, 1200, 1500	124