

## **STOREROOM TROLLEYS**

Highly variable and secure through the trademarked fetra-Insert-and-Bolt Principle to fix the shelves • Easy handling • Sectional/tubular steel construction • Powder coated blue RAL 5007 • Push handles on both sides, usable without handle • Frames with derived timber material boards housed in the frame, surface beech grain, detachable shelves with 15 mm rim, inserted as required in intervals of 120 mm horizontal, or tilted by 15 or 30° • 2 castors and 2 fixed wheels, wheels with solid rubber tyres, hubs with roller bearings • Castors with wheel locks





28000 | 28020



#### Clip board

Upright format DIN A 4, wood with paper clamp and pencil case. Fixing to top of end frame with clips.



#### Storage box

with writing plate  
Dimensions W x D x H =  
310 x 220 x 80 mm,  
writing plate tiltable, with  
extended handle protruding  
by 280 mm, powder coated  
blue RAL 5007.



#### Steps

tiltable, only for storeroom  
trolley 28220. Add-on set with  
2 steps, lifting automatically  
when released and standing  
firmly on the floor  
when under load. Thus the  
trolley is automatically locked.  
You can hold onto or lean  
against the safety handle pro-  
vided. Steps can be tilted when in  
rest position.  
Clearance between steps: 235  
mm, Height of steps: 515 mm.



28220

## 28000 | 28020

Storeroom trolley, modular  
system, tubular steel  
construction for screw  
connection. End frame with  
horizontally screwed on  
handlebar, powder coated blue  
RAL 5007.

Shelves made of derived  
timber material boards, surface  
with beech grain.

2 castor wheels and 2 fixed  
wheels, wheels with elastic  
solid rubber tyres 160 x 40 mm,  
hubs with roller bearings.

Castors with wheel locks,  
**according to the European  
Standard EN 1757-3.**

Capacity upper platform 120 kg.  
Shelf heights: 230/ 735 mm.

## 28220

Storeroom trolley as shelved  
trolley with horizontal or  
inclined, detachable shelves.  
Tubular/sectional steel design,  
powder-coated blue RAL 5007.

Shelves made of derived  
timber boards, surface beech  
grain, put into an angle steel  
frame with 15 mm high  
skirting. Detachable shelves  
variably insertable, distance  
between support rods 120 mm,  
possible angle when inclined,  
approx. 15 mm or approx. 30°.  
2 tubular handlebars.

2 castor wheels and 2 fixed  
wheels, wheels with elastic  
solid rubber tyres 160 x 40 mm,  
hubs with roller bearings.

Castors with wheel locks,  
**according to the European  
Standard EN 1757-3.**

Capacity per shelf 80 kg.

### Tip:

**Easily and conveniently drive  
by wheels with elasticated  
solid rubber tyres and ball  
bearings.**

|                                      | Order no. | Capacity<br>kg | Wheel-Ø<br>mm | Outside dimension<br>LxWxH mm | Platform size<br>LxW mm | Net weight<br>kg |  |
|--------------------------------------|-----------|----------------|---------------|-------------------------------|-------------------------|------------------|--|
| <b>Storeroom trolleys</b>            | 28000     | 300            | 160           | 1210 x 500 x 1140             | 1000 x 500              | 33               |  |
|                                      | 28020     | 300            | 160           | 1410 x 600 x 1140             | 1200 x 600              | 43               |  |
|                                      | 28220     | 400            | 160           | 1745 x 550 x 1525             | 1330 x 530              | 74               |  |
| <b>Additional shelves</b>            | 28224     | 80             | -             | -                             | 1330 x 530              | 13               |  |
| <b>Clip board</b>                    | 28222     | -              | -             | -                             | -                       | -                |  |
| <b>Storage box for trolley 28000</b> | 28003     | -              | -             | -                             | -                       | -                |  |
| <b>Storage box for trolley 28020</b> | 28023     | -              | -             | -                             | -                       | -                |  |
| <b>Storage box for trolley 28220</b> | 28223     | -              | -             | -                             | -                       | -                |  |
| <b>Steps</b>                         | 28225     | -              | -             | -                             | -                       | -                |  |
| <b>Elasticated tyres and bearing</b> | 12860     | -              | 160           | -                             | -                       | -                |  |

**Storeroom trolleys with steps**

Welded tubular and sectional steel, powder coated. Shelves made of derived timber material boards in angle steel frame, 12 mm high skirting.

2 castor and 2 fixed wheels, solid rubber tyres. Hubs with roller bearings.

Castors with wheel locks, according to the European Standard EN 1757-3.

Capacity upper and middle shelves 80 kg.

At the face ends wooden steps lifting automatically when released and standing firmly on the floor when under load, whereby the trolley is automatically locked. You can hold onto or lean against the safety handle provided. Steps can be tilted when in rest position.

**2105 | 2106**

Outside dimensions L x W x H:  
1320 x 610 x 1135 mm

**2107**

Outside dimensions L x W x H:  
1495 x 610 x 1900 mm

**2108**

Outside dimensions L x W x H:  
1495 x 610 x 1900 mm

**Tip:**

Easily and conveniently drive by wheels with elasticated solid rubber tyres and ball bearings.



2105



2106



2107



2108



Steps tilted

|   | Order no. | Capacity kg | Wheel-Ø mm | Platform size L x W mm | No. of shelves | Shelf heights mm     | Height of step mm | Clearance between steps | Net weight kg |
|---|-----------|-------------|------------|------------------------|----------------|----------------------|-------------------|-------------------------|---------------|
| <b>Storeroom trolleys</b>                               | 2105      | 250         | 125        | 1000 x 600             | 2              | 190, 820             | 515               | 235                     | 47            |
|   | 2106      | 250         | 125        | 1000 x 600             | 3              | 190, 510, 820        | 515               | 235                     | 59            |
|   | 2107      | 250         | 160        | 1000 x 600             | 3              | 240, 860, 1480       | 935               | 230                     | 73            |
|   | 2108      | 250         | 160        | 1000 x 600             | 4              | 240, 715, 1190, 1665 | 935               | 230                     | 86            |
| <b>Elasticated solid rubber tyres and ball bearings</b> | 12850     | -           | 125        | -                      | -              | -                    | -                 | -                       | -             |
|   | 12860     | -           | 160        | -                      | -              | -                    | -                 | -                       | -             |

**Accessories on page 92**

no bigger wheel Ø possible