

-First class monolithic polyamide 6 wheel, neutral color, corrosion resistant.


- Roller bearing


- Temperature range from -20°C to 80°C


- Maximum working speed 4 kmh


- Standard housing M80A

																Codes
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	Load cap. (kg)	(Weight) kg	

 <b>NPMMP-G06 G07</b>	<b>100</b>	<b>35</b>	133	100x85	80x60	10.5	42	-	-	-	-	-	-	<b>300</b>	0,89	G06 210 100035
	<b>125L</b>	<b>35</b>	161	100x85	80x60	10.5	44	-	-	-	-	-	-	<b>350</b>	1.00	G07 210 125035*
	<b>125</b>	<b>45</b>	159	140x110	105x80/75	11	65	-	-	-	-	-	-	<b>450</b>	1.76	G07 210 125045
	<b>150</b>	<b>45</b>	180	140x110	105x80/75	11	65	-	-	-	-	-	-	<b>500</b>	1,96	G07 210 150045
	<b>200</b>	<b>50</b>	240	140x110	105x80/75	11	65	-	-	-	-	-	-	<b>550</b>	2,53	G07 210 200050

 <b>NPMMPFR-G06 G07</b>	<b>100</b>	<b>35</b>	133	100x85	80x60	10.5	42	-	-	-	-	105	<b>300</b>	1.19	G06 214 100035
	<b>125L</b>	<b>35</b>	161	100x85	80x60	10.5	44	-	-	-	-	105	<b>350</b>	1.40	G07 214 125035*
	<b>150</b>	<b>45</b>	180	140x110	105x80/75	11	65	-	-	-	-	125	<b>500</b>	2.36	G07 214 150045
	<b>200</b>	<b>50</b>	240	140x110	105x80/75	11	65	-	-	-	-	125	<b>550</b>	3.03	G07 214 200050

 <b>NPMMPFA-G06 G07</b>	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	<b>200</b>	<b>50</b>	240	140x110	105x80/75	11	65	-	-	-	-	148	-	<b>550</b>	2.84	G07 212 200050	
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

 <b>NFMMP-G06 G07</b>	<b>100</b>	<b>35</b>	133	100x85	80x60	10.5	-	-	-	-	-	-	-	<b>300</b>	0,58	G06 220 100035
	<b>125L</b>	<b>35</b>	161	100x85	80x60	10.5	-	-	-	-	-	-	-	<b>350</b>	0.70	G07 220 125035*
	<b>125</b>	<b>45</b>	159	140x110	105x80/75	11	-	-	-	-	-	-	-	<b>450</b>	1.10	G07 220 125045
	<b>150</b>	<b>45</b>	180	140x110	105x80/75	11	-	-	-	-	-	-	-	<b>500</b>	1,27	G07 220 150045
	<b>200</b>	<b>50</b>	240	140x110	105x80/75	11	-	-	-	-	-	-	-	<b>550</b>	1.89	G07 220 200050